

Nickel Plated Brass Glands & Locknuts with Neoprene Rubber compression inserts & IP66 sealing



Type.	Thread Size.	Across corners.	Thread Length.	Capacity Dia (Min - Max.)
A2 M20 - 16	ISO M20	24.5mm	15mm	3.5 - 8.5 mm
A2 M20S	ISO M20	26.5mm	10mm	8.0 - 11.5 mm
A2 M20	ISO M20	30.0mm	10mm	11.0 - 13.5 mm
A2 M25	ISO M25	39.9mm	10mm	13.0 - 19.5 mm
A2 M32	ISO M32	45.5mm	10mm	19.0 - 25.5 mm
A2 M40	ISO M40	55.4mm	15mm	25.0 - 32.0 mm
A2 M50S	ISO M50	61.0mm	15mm	31.5 - 37.0 mm
A2 M50	ISO M50	66.5mm	15mm	36.5 - 43.0 mm
A2 M63S	ISO M63	77.6mm	15mm	42.5 - 50.0 mm
A2 M63	ISO M63	83.2mm	15mm	48.5 - 55.0 mm
A2 M75S	ISO M75	88.7mm	15mm	54.5 - 61.0 mm
A2 M75	ISO M75	94.2mm	15mm	60.5 - 67.0 mm

Nylon Glands & Locknuts with Neoprene Rubber compression inserts & IP68 sealing



Type.	Thread dia.	Across flats.	Thread Length.	Capacity Dia (Min - Max.)
PG 7.0	12.5 mm	15 mm	8 mm	3.0 - 6.5 mm
PG 9.0	15.2 mm	19 mm	8 mm	4.0 - 8.0 mm
PG 11.0	18.6 mm	22 mm	8 mm	5.0 - 10.0 mm
PG 13.5	20.4 mm	24 mm	9 mm	6.0 - 12.0 mm
PG 16.0	22.5mm	27 mm	11 mm	10.0 - 14.0 mm
PG 21.0	28.3 mm	33 mm	11 mm	13.0 - 18.0 mm
PG 29.0	37.0 mm	42 mm	11 mm	18.0 - 25.0 mm
PG 36.0	47.0 mm	53 mm	13 mm	22.0 - 32.0 mm
PG 42.0	54.0 mm	60 mm	13 mm	30.0 - 38.0 mm
PG 48.0	59.3 mm	65 mm	14 mm	34.0 - 44.0 mm