

# Tool Balancers - 2 to 14Kg capacity

**Capacity 2.0Kg - 14.0Kg  
Stroke 2500mm**



**Features:**

- ◆ Safety device prevents the load from dropping in the event of spring failure.
- ◆ Rugged construction, cast aluminium body.
- ◆ Adjustable capacity.
- ◆ Anti - friction cable guide.
- ◆ Adjustable stroke limiting device.
- ◆ Safety hook.
- ◆ Auxiliary safety cable.
- ◆ Stainless steel cable.

| Type No. | Capacity Kg. | Weight Kg. | Dim. Drg. |
|----------|--------------|------------|-----------|
| 9336     | 2 - 4        | 2.9        | 3         |
| 9337     | 4 - 6        | 3.2        | 3         |
| 9338     | 6 - 8        | 3.5        | 3         |
| 9339     | 8 - 10       | 3.7        | 3         |
| 9340     | 10 - 14      | 4.0        | 3         |

**Capacity 2.0Kg - 14.0Kg  
Stroke 2500mm  
With latching device.**

Specification and dimensions identical to across but fitted with additional device to stop the stroke by means of manual restriction as the load is raised.



**Features:**

- ◆ Safety device prevents the load from dropping in the event of spring failure.
- ◆ Rugged construction, cast aluminium body.
- ◆ Adjustable capacity.
- ◆ Anti - friction cable guide.
- ◆ Adjustable stroke limiting device.
- ◆ Safety hook.
- ◆ Auxiliary safety cable.
- ◆ Stainless steel cable.
- ◆ Latching device to hold load at different levels

| Type No. | Capacity Kg. | Weight Kg. | Dim. Drg. |
|----------|--------------|------------|-----------|
| 9346     | 2 - 4        | 3          | 3         |
| 9347     | 4 - 6        | 3.3        | 3         |
| 9348     | 6 - 8        | 3.6        | 3         |
| 9349     | 8 - 10       | 3.8        | 3         |
| 9350     | 10 - 14      | 4.2        | 3         |



