





- ① Copper conductor
- ② Rubber Insulation
- ③ Neoprene outer sheath

## FLATFLEX-N-500 NGFLGOU (300/500 V)

### Neoprene Flat cable

Part No	Cross Section mm <sup>2</sup>	Current Rating @ 30 Deg	CU Number kg/km	Outer Dimensions approx. (mm)	Weight kg/km	Plated Brass Gland Size
08014 0150 04	4 G 1.5	18A	58.0	17.0 x 6.4	190	12.2121
08014 0250 04	4 G 2.5	26A	96.0	20.7 x 7.8	280	12.2121
08014 0400 04	4 G 4	34A	154.0	24.8 x 9.1	402	12.2930
08014 0600 04	4 G 6	44A	230.0	27.9 x 9.9	540	12.2930
08014 1000 04	4 G 10	61A	384.0	33.3 x 11.2	775	12.3640
08014 1600 04	4 G 16	82A	614.0	38.7 x 13.0	1160	12.3640
08014 2500 04	4 G 25	108A	960.0	46.0 x 14.7	1560	8107
08014 3500 04	4 G 35	135A	1344.0	53.2 x 17.6	2175	8107
08014 5000 04	4 G 50	168A	1920.0	62.0 x 20.1	3020	8108
08014 7000 04	4 G 70	207A	2688.0	71.0 x 23.0	4325	8108
08014 9500 04	4 G 95	250A	3648.0	81.0 x 25.5	5120	8110
08014 1200 04	4 G 120	292A	4608.0	91.0 x 28.0	6340	8110
08014 0150 05	5 G 1.5	18A	72.0	21.5 x 6.4	240	12.2121
08014 0250 05	5 G 2.5	26A	120.0	26.0 x 7.8	355	12.2930
08014 0400 05	5 G 4	34A	192.0	32.0 x 9.0	520	12.3640
08014 0600 05	5 G 6	44A	288.0	34.7 x 9.9	700	12.3640
08014 1000 05	5 G 10	61A	480.0	41.5 x 11.2	985	12.4245
08014 1600 05	5 G 16	82A	768.0	50.0 x 13.0	1450	8107
08014 2500 05	5 G 25	108A	1200.0	60.0 x 16.0	2200	8108
08014 0150 07	7 G 1.5	18A	101.0	29.1 x 6.4	300	12.2930
08014 0250 07	7 G 2.5	26A	168.0	33.0 x 7.8	485	12.3640
08014 0400 07	7 G 4	34A	269.0	39.8 x 9.1	720	12.3640
08014 0600 07	7 G 6	44A	403.0	45.9 x 9.9	910	12.4245
08014 1000 07	7 G 10	61A	672.0	55.3 x 11.2	1385	8107
08014 1600 07	7 G 16	82A	1075.0	66.0 x 14.0	2345	8108
08014 2500 07	7 G 25	108A	1680.0	79.0 x 16.5	3240	8110
08014 3500 07	7 G 35	135A	2352.0	91.0 x 18.2	4140	8110
08014 0150 08	8 G 1.5	14A	115.0	32.0 x 6.4	340	12.3640
08014 0250 08	8 G 2.5	20A	192.0	38.0 x 7.8	510	12.3640
08014 0150 12	12 G 1.5	11A	173.0	47.5 x 7.0	550	12.4250
08014 0250 12	12 G 2.5	15A	288.0	54.8 x 8.2	810	8107
08014 0150 16	4 X 4 G 1.5	10A	231.0	45.0 x 15.0	1055	8107
08014 0250 16	4 X 4 G 2.5	13A	385.0	53.0 x 17.0	1465	8108
08014 0150 24	6 X 4 G 1.5	9A	346.0	55.0 x 12.5	1050	8107
08014 0250 24	6 X 4 G 2.5	12A	576.0	71.0 x 17.0	1920	8108

Other sizes are available on request

We reserve the right to amend all technical details without prior notification