



- ① Copper conductor
- ② PVC Insulation
- ③ Zinc-coated steel wire braid
- ④ PVC outer sheath

ROUNDFLEX 500-SY

Armoured Flexible PVC Control cable

Part No	Cross Section mm ²	Current Rating @ 30 Deg	CU Number kg/km	Outer Diameter approx. (mm)	Weight kg/km
08061 0050 03	3 G 0.5	10A	15.0	8.1	95
08061 0050 04	4 G 0.5	10A	19.2	8.5	107
08061 0050 05	5 G 0.5	10A	24.0	9.2	123
08061 0050 07	7 G 0.5	10A	33.6	9.7	147
08061 0050 12	12 G 0.5	10A	58.0	11.9	213
08061 0075 02	2 X 0.75	13A	14.4	8.2	97
08061 0075 03	3 G 0.75	13A	21.6	8.5	108
08061 0075 04	4 G 0.75	13A	28.8	9.2	126
08061 0075 05	5 G 0.75	13A	36.0	9.7	146
08061 0075 07	7 G 0.75	13A	50.0	10.3	172
08061 0075 12	12 G 0.75	13A	86.0	12.9	260
08061 0100 02	2 X 1	16A	19.2	8.5	106
08061 0100 03	3 G 1	16A	28.8	8.8	119
08061 0100 04	4 G 1	16A	39.4	9.5	141
08061 0100 05	5 G 1	16A	48.0	10.1	164
08061 0100 07	7 G 1	16A	67.0	11.0	200
08061 0100 12	12 G 1	16A	115.0	13.9	309
08061 0150 02	2 X 1.5	20A	29.0	9.3	126
08061 0150 03	3 G 1.5	20A	43.0	9.7	151
08061 0150 04	4 G 1.5	20A	58.0	10.2	173
08061 0150 05	5 G 1.5	20A	72.0	11.1	202
08061 0150 07	7 G 1.5	20A	101.0	11.9	248
08061 0150 12	12 G 1.5	20A	173.0	15.4	396
08061 0250 03	3 G 2.5	25A	72.0	11.1	208
08061 0250 04	4 G 2.5	25A	96.0	12.1	249
08061 0250 05	5 G 2.5	25A	120.0	13.2	295
08061 0250 07	7 G 2.5	25A	168.0	14.3	373
08061 0250 12	12 G 2.5	25A	288.0	18.2	586
08061 0400 04	4 G 4	36A	154.0	14.0	348
08061 0400 05	5 G 4	36A	192.0	15.1	410
08061 0400 07	7 G 4	36A	269.0	16.4	519

Other sizes are available on request

We reserve the right to amend all technical details without prior notification

