



- ① Copper conductor
- ② PVC Insulation
- ③ PVC outer sheath

ROUNDFLEX HV 0.6/1 kV

Flexible PVC Control cable 600/1000V

Part No	Cross Section mm ²	Current Rating @ 30 Deg	CU Number kg/km	Outer diameter approx. (mm)	Weight kg/km
08051 0050 03 HV	3 G 0.5	10A	14.4	7.0	88
08051 0050 04 HV	4 G 0.5	10A	19.2	7.5	100
08051 0050 05 HV	5 G 0.5	10A	24.0	8.3	115
08051 0050 07 HV	7 G 0.5	10A	34.0	9.0	136
08051 0050 12 HV	12 G 0.5	10A	58.0	12.0	200
08051 0500 18 HV	18 G 0.5	10A	86.0	14.0	280
08051 0075 02 HV	2 X 0.75	13A	14.4	8.3	80
08051 0075 03 HV	3 G 0.75	13A	21.6	8.7	90
08051 0075 04 HV	4 G 0.75	13A	29.0	9.2	99
08051 0075 05 HV	5 G 0.75	13A	36.0	9.9	130
08051 0075 07 HV	7 G 0.75	13A	50.0	10.7	170
08051 0075 12 HV	12 G 0.75	13A	86.0	13.4	257
08051 0075 18 HV	18 G 0.75	13A	130.0	15.4	362
08051 0100 02 HV	2 X 1	16A	19.2	8.6	96
08051 0100 03 HV	3 G 1	16A	29.0	9.0	108
08051 0100 04 HV	4 G 1	16A	38.4	9.6	126
08051 0100 05 HV	5 G 1	16A	48.0	10.4	140
08051 0100 07 HV	7 G 1	16A	67.0	11.7	190
08051 0100 12 HV	12 G 1	16A	115.0	14.0	290
08051 0100 18 HV	18 G 1	16A	173.0	16.1	405
08051 0150 02 HV	2 X 1.5	20A	29.0	9.6	99
08051 0150 03 HV	3 G 1.5	20A	43.0	10.1	110
08051 0150 04 HV	4 G 1.5	20A	58.0	10.8	140
08051 0150 05 HV	5 G 1.5	20A	72.0	11.7	170
08051 0150 07 HV	7 G 1.5	20A	101.0	12.6	220
08051 0150 12 HV	12 G 1.5	20A	173.0	16.1	320
08051 0150 18 HV	18 G 1.5	20A	259.0	18.8	510
08051 0250 02 HV	2 X 2.5	25A	48.0	10.8	155
08051 0250 03 HV	3 G 2.5	25A	72.0	11.3	176
08051 0250 04 HV	4 G 2.5	25A	96.0	12.2	205
08051 0250 05 HV	5 G 2.5	25A	120.0	13.3	251
08051 0250 07 HV	7 G 2.5	25A	168.0	14.4	331
08051 0250 12 HV	12 G 2.5	25A	288.0	18.7	553
08051 0250 18 HV	18 G 2.5	25A	432.0	22.0	788

Other sizes are available on request

We reserve the right to amend all technical details without prior notification

