



- ① Copper conductor
- ② PVC Insulation
- ③ Tinned copper screen
- ④ PVC outer sheath

ROUND FLEX HV-CY 0.6/1 kV

Flexible Screened PVC Control cable 600/1000V

Part No	Cross Section mm ²	Current Rating @ 30 Deg	CU Number kg/km	Outer Diameter approx. (mm)	Weight kg/km
08051 0050 03 HV-CY	3 G 0.5	10A	45.0	10.4	181
08051 0050 04 HV-CY	4 G 0.5	10A	54.0	11.0	210
08051 0050 05 HV-CY	5 G 0.5	10A	62.0	11.6	239
08051 0050 07 HV-CY	7 G 0.5	10A	76.0	12.3	274
08051 0050 12 HV-CY	12 G 0.5	10A	131.0	14.9	398
08051 0500 18 HV-CY	18 G 0.5	10A	175.0	17.0	522
08051 0075 02 HV-CY	2 X 0.75	13A	46.0	10.5	183
08051 0075 03 HV-CY	3 G 0.75	13A	56.0	10.9	210
08051 0075 04 HV-CY	4 G 0.75	13A	67.0	11.4	238
08051 0075 05 HV-CY	5 G 0.75	13A	78.0	12.1	272
08051 0075 07 HV-CY	7 G 0.75	13A	97.0	12.9	315
08051 0075 12 HV-CY	12 G 0.75	13A	168.0	15.8	464
08051 0075 18 HV-CY	18 G 0.75	13A	229.0	18.0	616
08051 0100 02 HV-CY	2 X 1	16A	52.0	10.8	198
08051 0100 03 HV-CY	3 G 1	16A	66.0	11.2	228
08051 0100 04 HV-CY	4 G 1	16A	79.0	11.8	261
08051 0100 05 HV-CY	5 G 1	16A	93.0	12.6	300
08051 0100 07 HV-CY	7 G 1	16A	117.0	13.3	335
08051 0100 12 HV-CY	12 G 1	16A	204.0	16.4	522
08051 0100 18 HV-CY	18 G 1	16A	280.0	18.7	687
08051 0150 02 HV-CY	2 X 1.5	20A	69.0	11.8	243
08051 0150 03 HV-CY	3 G 1.5	20A	87.0	12.3	273
08051 0150 04 HV-CY	4 G 1.5	20A	102.0	13.0	290
08051 0150 05 HV-CY	5 G 1.5	20A	125.0	13.9	352
08051 0150 07 HV-CY	7 G 1.5	20A	180.0	15.0	448
08051 0150 12 HV-CY	12 G 1.5	20A	281.0	18.7	690
08051 0150 18 HV-CY	18 G 1.5	20A	391.0	21.8	938
08051 0250 02 HV-CY	2 X 2.5	25A	112.0	12.1	202
08051 0250 03 HV-CY	3 G 2.5	25A	123.0	13.5	354
08051 0250 04 HV-CY	4 G 2.5	25A	168.0	14.6	413
08051 0250 05 HV-CY	5 G 2.5	25A	204.0	14.6	515
08051 0250 07 HV-CY	7 G 2.5	25A	265.0	17.0	619
08051 0250 12 HV-CY	12 G 2.5	25A	421.0	21.7	936
08051 0250 18 HV-CY	18 G 2.5	25A	596.0	26.0	958

Other sizes are available on request

We reserve the right to amend all technical details without prior notification

